



PrintPoint® 3000




The next generation

in printer technology has arrived. The PrintPoint 3000 provides merchants with the most efficient, convenient and reliable thermal printer on the market. With a print speed of 20 lines per second, the PrintPoint 3000 is one of the fastest thermal printers in the industry. Its crisp, legible receipts print quickly and quietly.

Featuring a patented drop-in paper-loading system, the PrintPoint 3000 is hassle-free. Merchants can simply open the cover, drop in paper and print. There is virtually no failure in the field due to paper jams. With its small footprint and modular design, the PrintPoint 3000 provides maximum convenience, and it is compatible with a variety of industry terminals, enhancing versatility at the merchant site.



PrintPoint 3000



Superior Reliability

- Reduces long-term merchant-support expenses
- 12-month warranty provides peace of mind

Unbeatable Performance

- Print speed of 20 lines per second is one of the fastest in the industry
- Crisp, legible receipts print quietly and smoothly
- Print path eliminates failures due to paper jams

Maximum Merchant Efficiency

- Plug-and-play installation is virtually error-proof
- Simple printer-settings menu makes everyday operation easy
- Drop-in paper-loading system is quick and hassle-free

Versatility at the Merchant Site

- 13 international character sets support all merchant printing requirements
- Modular design is compatible with several point-of-sale terminals

Compact Design

- Small footprint provides the greatest convenience
- Base or wall mounting saves valuable counterspace

Specifications

- **Paper Size:** 2¼" wide thermal paper roll.
- **Mechanism:** thermal, fixed print head.
- **Print speed:** 20 lines per second.
- **Buffer:** 4 KB.
- **Mechanical reliability/print-head life:** 17 million lines.
- **Copies:** 1, 2 or 3.
- **Characters per line:** 24, 32 or 42.
- **Resolution:** 384 dots per line, 8 dots/mm.
- **Interface:** serial, RS-232.
- **Baud rate:** 1,200, 2,400, 4,800, 9,600 or 19,200.
- **Physical:** 3.84 in. (96 mm) H X 5.72 in. (143 mm) W X 4.46 in. (113.4 mm) L, 1.32 lb. (.594 kg).
- **Net shipping weight (including power adapter):** 7.0 lb. (3.15 kg).
- **Power:** 120 VAC, 60 Hz, 78 W.
- **Environmental:** Temperature: 32° to 122°F (0° to 50°C), Operating humidity: 20% to 85%; noncondensing.
- **Warranty:** Standard 12-month warranty.