

# DataCard Silent Printer

## SPECIFICATIONS

- |   |   |
|---|---|
| <ul style="list-style-type: none"><li>▪ <b>Physical dimensions:</b><ul style="list-style-type: none"><li>○ 4.0 in. wide x 7.8 in. deep x 6.2 in high (10.1 cm x 19.7 cm x 15.7 cm)</li></ul></li><li>▪ <b>Weight:</b><ul style="list-style-type: none"><li>○ 1.25 lbs. (0.57 kg)</li></ul></li><li>▪ <b>Electrical Requirements:</b><ul style="list-style-type: none"><li>○ 24 VDC +/- 10% or supplied AC adapter (use supplied DataCard powerpack)</li></ul></li><li>▪ <b>Power Consumption:</b><ul style="list-style-type: none"><li>○ 0.5 W non-operating</li><li>○ 12 W printing at 12 lines per second</li></ul></li><li>▪ <b>Environmental Requirements:</b><ul style="list-style-type: none"><li>○ <b>Operating Temperature:</b> 50 F to 104 F (10 C to 40 C)</li><li>○ <b>Storage Temperature:</b> 14 F to 140 F (10 C to 60 C)</li><li>○ <b>Humidity:</b> 30% to 80% relative humidity, non-condensing</li></ul></li></ul> | <ul style="list-style-type: none"><li>▪ <b>Serial Interface:</b><ul style="list-style-type: none"><li>○ <b>Signal levels:</b> RS 232-C compatible</li><li>○ <b>Data formats:</b> asynchronous</li><li>○ <b>Handshaking:</b> RTS</li><li>○ <b>Baud Rate:</b> 1200, 2400, 4800, 9600</li><li>○ <b>Data:</b> 7 or 8 bits; even, odd, space and no parity</li><li>○ <b>Connector:</b> RJ-11, 6 conductor</li></ul></li><li>▪ <b>Receipt Paper:</b><ul style="list-style-type: none"><li>○ <b>Type:</b> Direct thermal</li><li>○ <b>Width:</b> 2.44 in +/- 0.0197 in. (62 mm +/- 0.5 mm)</li><li>○ <b>Length:</b> 285 ft. (86.9 m)</li><li>○ <b>Thickness:</b> 0.0002 in. to 0.009 in. (0.051 mm to 0.229 mm)</li><li>○ <b>Core Size:</b> 1 in. (25.4 mm)</li><li>○ <b>20% activation temperature:</b> &gt;140 F (&gt;60 C)</li><li>○ <b>Exposure Temperature:</b> 176 F (80 C) - programmable</li><li>○ <b>Copy capability:</b> 1,2, or 3 copies; automatic duplicate</li></ul></li></ul> |
|---|---|